TRANSIENT-PHASE PWM POWER SUPPLY AND METHOD

CLAIM OF PRIORITY

[1]   This application claims priority to U.S. Provisional Application Serial No. 60/460,460, filed on April 4, 2003, which is incorporated by reference.

BACKGROUND OF THE INVENTION

[2]   Today's electronic systems typically require a relatively high amount of current from one or more highly regulated power supplies. A typical computer system will draw 50-60 Amperes (A) (laptop) or 80-120 As (desktop/server) from a 1.2 to 1.3 volt (v) power supply. In the past, linear power supplies have been used, but a significant amount of power is typically dissipated across the pass element. As a result, pulse-width modulated (PWM) switching power supplies were introduced to provide power in a more efficient manner. Switching power supplies dissipate less power than linear power supplies because the drive transistors operate in either full-on or full-off mode. Specifically, in the full-on mode, the voltage drop across a drive transistor is minimal, and in the full-off mode, no current flows through the drive transistor. Therefore, in the full-on mode, there is low power dissipation in the drive transistor even at a relatively high current.

[3]   To provide relatively high output currents, conventional PWM power supplies include one or more main channels or phases. Each phase is driven by a PWM controller chip and includes a driver, a pair of output drive transistors arranged in a push/pull configuration, and a filter inductor, which is coupled to a filter capacitor which is common to all phases. Because the drive transistors provide relatively high current, they are relatively high-power devices that, in turn, have relatively slow on/off times. Therefore, it is desirable to drive a main phase with a relatively long pulse width so that the high-power drive transistors have sufficient time to turn on and operate in the

full-on mode. That is, for the best efficiency, the pulse width should be much greater –
for example, at least ten times greater – than the longer of the drive transistors' on and
off times.

[4]   Of course, without proper filtering, longer on times at relatively high

5   currents will typically cause the drive transistors to rather quickly, overcharge the filter
capacitor and, thus, drive the output voltage above the regulated range. One way to
prevent this over-voltage situation would be to drive the transistors using relatively short
pulse widths. But as stated above, because these transistors have relatively slow on/off
times, such operation would be very inefficient.

10   [5]   Consequently, a filter inductor is typically placed between the drive
transistors and the filter capacitor. From the standard inductance equation $V=LdI/dT$,
one can see that $dI/dT = V/L$, where V is the voltage across an inductor, L is the
inductance, and I is the current through the inductor. Therefore, one selects the size of
the inductor such that dI/dT is small enough to allow the relatively long pulse widths to

15   drive the transistors without overshooting the regulated voltage. Although this allows
the drive transistors to operate efficiently and to provide large amounts of power, the
response time of each main phase to transients (caused by sudden demands for either
an increase or a decrease in power from the power supply) is relatively slow.
Therefore, such transients can cause the power supply voltage to temporarily go out of

20   the regulated range, *i.e.,* cause the PWM power supply to temporarily lose regulation
and allow the supply voltage to spike. Unfortunately, if such a transient is large enough
or long enough, it may cause a malfunction such as corruption of data stored in a
memory.

[6]   To reduce the size of the drive transistors and filter inductors, and thus to

25   allow an increase in the power supply's transient response, a typical PWM power supply
includes multiple main phases that, in a steady state condition, operate in an alternating

2

switching pattern such that at least one main phase is always on. This allows the different main phases to share the power supplying duties to the load. Although this sharing requires more circuitry, it allows faster drive transistors and smaller filter inductors to be used. But unfortunately, even a multiple-main-phase PWM power

5   supply is often unable to prevent relatively fast transients from occurring on the regulated power supply voltage.

[7]   Another way to reduce the magnitude of occurrences of power-supply transients is to use a larger filter capacitor that has a relatively low equivalent series resistance (ESR) and an acceptable high-frequency response. However, such a filter

10   capacitor take is often relatively large and expensive.

[8]   Alternatively, one can add a linear regulator to a PWM regulator to reduce the magnitude of occurrences of undesirable transients. The linear regulator, which is less efficient but has a faster response time than the PWM regulator, is activated only when a transient occurs to provide the fast correction response. This solution is

15   described in detail in U.S. Patent No. 5,926,384 to Jochum et al. But problems with this solution include the complexity and space requirements of adding a linear regulator, and also the inefficiency of dissipating power across the linear regulator's pass element.

SUMMARY OF THE INVENTION

[9]   In one aspect of the invention regulator comprises an output node

20   operable to provide a regulated supply voltage, a first main-phase drive circuit operable to provide a first main load current to the output node and having an on time and an off time, and a first transient-phase drive circuit operable to provide a first transient load current to the output node and having an on time and an off time that are respectively less than the on and off times of the first main-phase drive circuit.

25   [10]   By providing such a regulator, transients on the regulated supply can be reduced or eliminated by engaging a faster drive phase that can supply the transient

3

current until the slower main drive phase is able to modify its current to the load as appropriate.

BRIEF DESCRIPTION OF THE DRAWINGS

[11]   The foregoing aspects and many of the attendant advantages of this

5   invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

[12]   **FIG. 1** is schematic diagram of a PWM power supply in accordance with an embodiment of the invention;

10   [13]   **FIG. 2** is a timing diagram of voltage pulses for the phase drivers of the PWM power supply of **FIG. 1** in accordance with an embodiment of the invention; and

[14]   **FIG. 3** is a block diagram of a typical electronic system that includes the PWM power supply of **FIG. 1** in accordance with an embodiment of the invention.

DETAILED DESCRIPTION

15   [15]   The following discussion is presented to enable a person skilled in the art to make and use the invention. The general principles described herein may be applied to embodiments and applications other than those detailed below without departing from the spirit and scope of the present invention. The present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent

20   with the principles and features disclosed or suggested herein.

[16]   **FIG. 1** shows a schematic diagram of a PWM power supply *100* in accordance with an embodiment of the invention. The PWM power supply *100* of **FIG. 1** includes a pulse-width modulator *105*, four drive circuits *110*, *120*, *130*, and *140*, along with corresponding filter inductors *111*, *121*, *131*, and *141*, a filter capacitor *150*,

25   and a feedback circuit *152*. The drive circuits *110* and *120* represent two main

4

phases and the drive circuits *130* and *140* represent two fast phases. The PWM power

supply *100* is typically supplied by an unregulated AC power supply (not shown) and

typically drives an electronic load (also, not shown) requiring a highly regulated voltage

supply, such as, for example a central processing unit of a typical computer system.

5   The PWM modulator *105* activates the drive circuits *110*, *120*, *130*, and *140* based on

the feedback from the feedback circuit *152*.

[17]   The pulse-width modulator *105* is well known in the art and will not be

described in great detail herein. For the purposes of this discussion, the pulse-width

modulator *105* of **FIG. 1** is operable to provide voltage pulses of varying width to each of

10   the phase drive circuits *110*, *120*, *130*, and *140* according to the current demanded by a

load connected to the PWM power supply *100*.

[18]   In the embodiment shown in **FIG. 1**, the PWM power supply *100* includes

two main phase drive circuits (*110* and *120* in **FIG. 1**) but may include more in order to

provide the necessary current for larger loads. As stated above, the drive circuits *110*

15   and *120* work together in tandem to provide a majority of the power requirements

demanded by the load. Different from prior art, however, the PWM power supply *100* of

FIG. 1 includes at least one fast phase drive circuit, here two fast drive circuits *130* and

140.

[19]   Each drive circuit *110*, *120*, *130*, and *140*, whether it represents a main

20   phase or a fast phase, comprises a driver *115* and two NMOS drive transistors *116* and

117 coupled in a push/pull configuration. Only the components of the first main phase

drive *110* are labeled in **FIG. 1** for clarity of illustration.

[20]   Because the main drive circuits *110* and *120* provide the bulk of the power

to the load (not shown), the output transistors *116* and *117* of these drive circuits are

25   relatively large to provide relatively large currents to the load. But because they are

relatively large, the on/off times of these output transistors *116* and *117* are relatively slow. Consequently, the PWM circuit *105* drives these transistors with relatively long pulse widths for maximum efficiency, and the filter inductors *111* and *120* are relatively large, for example on the order of 500 nanohenries (nH), to prevent such long pulse

5   widths from oversupply the load. But the long on/off times and large inductors cause the drive circuits *110* and *120* to have relatively slow response times, often too slow to prevent or reduce transients in the regulated voltage Vreg.

[21]   The PWM supply *100* also includes two fast drive circuits *130* and *140* for preventing or reducing transients in Vreg. The transistors *116* and *117* of the

10   circuits *130* and *140* are smaller, and thus have faster on/off times, than the transistors in the drive circuits *110* and *120*. Consequently, the PWM circuit *105* can drive these transistors with relatively short pulse widths and still maintain maximum efficiency, and the filter inductors *131* and *141* are relatively small, for example on the order of 50 nH and 5nH, respectively, to allow the circuits *130* and *140* to quickly respond to transients

15   in Vreg. Once the transient has dissipated to a predetermined level, the PWM circuit *105* can deactivate the drive circuits *130* and *140* either together or separately.

[22]   Still referring to **FIG. 1**, one can use the relation V = Ldi/dt to determine the values of the inductors *130* and *140* based on the values of expected transients, where V is the voltage across the inductor, L is the inductance, and di/dt is the rate of

20   change of current through the inductor. For example, assume that two types of transients are expected, a first transient caused by the load suddenly increasing its current draw by 1×10^8 A per second, and a second transient caused by the load suddenly increasing its current draw by 1×10^9 A per second. Also assume that ideally Vreg = 1.2 V, the drains of the transistors *116* in the circuits *130* and *140* are coupled to

25   a 6.2 V supply, and the gates of these transistors *116* are conventionally overdriven

6

such that the full 6.2 V appears at their sources. Therefore, from the above relation, L = $(6.2 - 1.2)/(1 \times 10^8)$ = 50 nH for the inductor 131 and L = $(6.2 - 1.2)/(1 \times 10^9)$ = 5 nH.

[23]   Of course, the PWM power supply 100 can include more or fewer fast drive circuits such as the circuits 130 and 140, and these circuits can have inductors with different inductance values. For example, the supply 100 can have a number of drive circuits each having an inductor that is an order of magnitude smaller than the inductor of the preceding drive circuit.

[24]   Still referring to FIG. 1, the feedback circuit 152 provides a feedback signal that the PWM circuit 105 uses to determine what drive circuit or drive circuits to activate. For example, under normal operation where no transients appear on Vreg, the circuit 105 may alternately activate the main-phase drive circuits 110 and 120 and deactivate the fast-phase drive circuits 130 and 140. In response to a transient, however, the circuit 105 may activate one or both of the fast-phase drive circuits 130 and 140 in addition to the main-phase drive circuits 110 and 120 until the transient is reduced to a predetermined level. That is, the activated fast drive circuit(s) 130 and 140 provide(s) a "shot" of current to the load (not shown in FIG. 1) to reduce or eliminate the transient until the slower main drive circuits 110 and 120 are able to provide the new load current.

[25]   In one embodiment, the feedback circuit 152 operates as a multi-window comparator that causes the PWM circuit 105 to activate the fast drive circuits 130 and 140 based on the level of Vreg. For example, assume that ideally Vreg = 1.2 V, the inductors 111 and 121 equal 500 nH, the inductor 131 equals 50 nH, and the inductor 141 equals 5 nH. The feedback circuit 152 can be designed such that the PWM circuit 105 activates the main drive circuits 110 and 120 if Vreg moves out of the range 1.19 – 1.21, activates the fast drive circuit 130 (in addition to the main drive circuits 110 and

120) if Vreg moves out of the range 1.15 – 1.25 V, and activates the fast drive circuit **140** (in addition to the drive circuits **110**, **120**, and **130**) if Vreg moves out of the range 1.10 – 1.30 V. The PWM **105** may also deactivate the fast drive circuits **140** and **130** when Vreg returns to within the ranges 1.10 – 1.30 V and 1.15 – 1.25 V, respectively.

5   Of course when Vreg moves out of the range 1.19 – 1.21, the PWM **105** alternately activates the main drive circuits **110** and **120**. Typically, Vreg does move out of this range regularly so that the drive circuits **110** and **120** are active for at least a portion of each cycle.

[26]   Still referring to **FIG. 1**, other embodiments of the PWM power supply **110**
10   are contemplated. For example, the feedback circuit **152** may be incorporated within the PWM circuit **105**. Further, the feedback circuit **152** may implement one or more asymmetrical windows about Vreg, or may implement another technique for providing transient information to the PWM circuit **105**.

[27]   **FIG. 2** is a timing diagram showing how the PWM supply **100** of **FIG. 1**
15   responds to transients in the regulated supply voltage Vreg according to an embodiment of the invention. The plot **200** shows the load current Iload drawn from the Vreg terminal of the supply **100**. The sudden peaks **205,** which occur when power requirements of the load are higher, can cause transients in Vreg, thus causing Vreg to temporarily change from its ideal level. The plots **210**, **220**, **230**, and **240** respectively
20   indicate when the drive circuits **110**, **120**, **130**, and **140** are active (logic high) and inactive (logic low). .

[28]   During times of non-peak Iload, the main drive circuits **110** and **120** are alternately active, and the fast drive circuits **130** and **140** are inactive. That is, the circuit **110** is on while the circuit **120** is off, and vice versa. Conversely, during
25   times **205** of peak Iload, all of the drive circuits **110**, **120**, **130**, and **140** that would

otherwise be inactive are on for various periods of time *216*, *226*, *235*, and *245*,

respectively. Generally, the fastest drive circuit, here the drive circuit *140*, is on for the

shortest time, and the slowest drive circuit, here the drive circuit *110*, is on for the

longest time. The reason for this is that the faster the drive circuit, the smaller the drive

5   transistors *116* and *117* associated filter inductor (**FIG. 1**), and thus the more quickly the

current provided by the drive circuit reaches a desired maximum value. Consequently,

if the drive circuit is on for too long, the current through the drive transistors may grow

large enough to damage the drive circuit.

[29]   Still referring to **FIG. 2**, as the number of fast drive circuits increases, the

10   transient response time of the PWM supply *100* and the need for a large filter capacitor

150 (**FIG. 1**) decreases. Therefore, one can reduce the size of, and theoretically

eliminate, the filter capacitor *150* by including an adequate number of fast drive circuits

(with the appropriate values for the filter inductors) in the PWM power supply *100*, and

can attain a transient response time on the order of nanoseconds or less.

15   [30]   **FIG. 3** is a block diagram of an electronic system, here a computer

system, that incorporates the PWM power supply *100* of **FIG. 1** in accordance with an

embodiment of the invention. The PWM power supply *100* receives DC voltage Vin

from a main power supply *300.* Vin may be a regulated or unregulated, but is higher

than Vreg. The main supply 400 may generate Vin from an AC line voltage (*e.g.*, 120

20   VAC) or from another AC or DC voltage. A processor such as a CPU *305* receives

power from the PWM power supply *100*. The CPU is communicatively coupled to a

system bus *310*. The system bus *310* is also communicatively coupled to a system

memory *320* that may comprise ROM *321*, RAM *322* and firmware *323*. Additionally,

the system bus *310* is communicatively coupled to one or more I/O devices *330* and

335. The PWM power supply *100* may also power the system memory *320* and one or more I/O devices *330* and *335*.